

## **WE MAKE** LIFT TRUCKS **WITH HEART**

We delivered our first heavy-duty lift truck to a special customer in 1959. We put our heart into that first delivery, making the truck with great care and craftsmanship, looking after the delivery and working life of our first-born to make sure that customer was more than pleased.

Our attitude is exactly the same today. We now sell and service our lift trucks all over the world as part of Konecranes, the world's leading provider of smarter lifting solutions. Visit our production facilities and you'll find a close-knit community of Konecranes people with a common passion: making the hardest-working, longest-lived lift trucks in the world. We live and breathe lift trucks.

#### Konecranes Lifttrucks AB

MODEL NAME

SMV 2115 TB3

SMV 2518 TB3

Box 103, SE-285 23 Markaryd, Sweden Tel. +46 433 73300. Fax +46 433 73310 E-mail: info.lifttrucks@konecranes.com www.konecraneslifttrucks.se www.konecranes.com **Reach stackers for** container handling, 10 to 45 tons



MODEL NAME	CAPACITY	WHEELBASE
MV/ 109 TD6	10 9 5 tone	5000 mm

21-15-5 tons


25-18-8 tons

WHEELBASE 5500 mm

5500 mm



MODEL NAME	CAPACITY	WHEELBASE	MODEL NAME
SMV 4127 TB5 (TB6)*	41-27-14 tons	6400 mm	SMV 4542 TB5
SMV 4527 TB5 (TB6)*	45-27-14 tons	6400 mm	SMV 4542 TBX5*
SMV 4531 TB5 (TB6)*	45-31-16 tons	6400 mm	SMV 4543 TB5




EL NAME	CAPACITY	WHEELBASE
4535 TB5 (TB6)*	45-35-20 tons	6400 mm
4535 TBX5**	45-37-24 tons	6400 mm
4537 TB5	45-37-19 tons	6400 mm
4537 TBX5**	45-41-28 tons	6400 mm



SMV 4543 TBX5**	

45			
45	35		
45	35	20 (24)	
45	35	20 (24)	
45	35	20 (24)	

AME	CAPACITY	WHEELBASE
5 TB5 (TB6)*	45-35-20 tons	6400 mm
5 TBX5**	45-37-24 tons	6400 mm
7 TB5	45-37-19 tons	6400 mm
7 TBX5**	45-41-28 tons	6400 mm



45-42-24 tons

45-44-30 tons

WHEELBASE

7250 mm


7250 mm

7500 mm


\*\*TBX = Capacity with support jacks engage

MODEL NAME	CAPACITY	WHEELBASE	MODEL NAME	CAPACITY
SMV 4545 TB5	45-45-37 tons	8000 mm	SMV 4537 CB5	45-37-22 tons
SMV 4545 TBX5**	45-45-45 tons	8000 mm	SMV 4537 CBX5	45-40-28 tons
			SMV 4538 CB5	45-38-23 tons
			SMV 4538 CRX5***	45-40-32 tons

## **Reach stackers for** intermodal handling, 41 to 45 tons



MODEL NAME	CAPACITY	WHEELBASE
SMV 4123 CB5	41-23-9 tons	6400 mm
SMV 4527 CB5	45-27-13 tons	6400 mm
SMV 4531 CB5	45-31-16 tons	6400 mm
SMV 4531 CBX5***	45-33-20 tons	6400 mm
SMV 4533 CB5	45-33-16 tons	6400 mm
SMV 4533 CBX5***	45-37-24 tons	6400 mm



DEL NAME	CAPACITY	WHEELBASE	MODEL
/ 4537 CB5	45-37-22 tons	7250 mm	SMV 454
/ 4537 CBX5	45-40-28 tons	7250 mm	
/ 4538 CB5	45-38-23 tons	7500 mm	SMV 454
/ 4538 CBX5***	45-40-32 tons	7500 mm	
			SMV 454

#### **Reach stackers for industrial** handling, 35 to 80 tons



\*\*TBX = Capacity with support jacks engager

\*\*\*CBX = Capacity with support jacks engaged

VIE	CAPACITY	WHEELBASE	MODEL NAME	CAPACITY	WHEELE
CB5	41-23-9 tons	6400 mm	SMV 4545 CB5	45-45-33 tons	8000 m
CB5	45-27-13 tons	6400 mm	SMV 4545 CBX5***	45-45-45 tons	8000 m
CDE	45 21 16 tops	6400 mm			

### **Reach stackers for barge** handling, 45 tons



E	MODEL NAME	CAPACITY	WHEE
	SMV 4542 TB4 BH	45-37-23 tons (yard)	7500
		43-30-18 tons (barge)	7500
	SMV 4542 TBX4 BH**	45-41-31 tons (yard)	7500
		45-37-26 tons (barge)	7500
	SMV 4545 TB3 BH	45-45-35 tons (yard)	9000
		45-37-30 tons (barge)	9000



#### Container ports and terminals

- Intermodal and railroads

- Concrete, brick and rock
- Wood, pulp and paper

- · Oil and gas Wind power
- Waste-to-energy



8000 mm

MODEL NAME	CAPACITY	WHEELBASE
SMV 4127	35-50 tons	6400 mm
SMV 4527	35-50 tons	6400 mm
SMV 4531	35-50 tons	6400 mm
SMV 4535	35-50 tons	6400 mm
SMV 4542	40-60 tons	7250 mm

40-80 tons

#### **REACH STACKERS**



- Transport and logistics
- Trimodal river handling
- · Steel, aluminum and mining

- Automotive
- Heavy and general industry
- Shipyards
- Nuclear

# **TRUCKS**

**10-33** tons



LIFT TRUCKS

8-10 tons

26-45 tons

10-45 tons (container) 41-45 tons (intermodal) 35-80 tons (industrial)















Fork lift trucks, 10 to 18 tons



DEL NAME	CAPACITY	WHEELBASE
V 10-600 BS	10 tons at 600 mm	2800 mm
V 12-600 BS	12 tons at 600 mm	2800 mm
V 10-600 B	10 tons at 600 mm	3000 mm
V 12-600 B	12 tons at 600 mm	3000 mm



Visit .	11112	
IODEL NAME	CAPACITY	WHEELBASE
MV 12-1200 B	12 tons at 1200 mm	3500 mm
MV 16-600 B	16 tons at 600 mm	3500 mm
MV 16-900 B	16 tons at 900 mm	3500 mm



MODEL NAME	CAPACITY	WHEELBASE
SMV 18-1200 B	18 tons at 1200 mm	4000 mm
SMV 20-1200 B	20 tons at 1200 mm	4000 mm



MODEL NAME	CAPACITY	WHEELBASE
SMV 28-1200 B	28 tons at 1200 mm	4500 mm
SMV 32-1200 B	32 tons at 1200 mm	4750 mm
SMV 33-1200 B	33 tons at 1200 mm	4750 mm



MODEL NAME	CAPACITY	WHEELBASE
SMV 37-1200 B	37 tons at 1200 mm	5000 mm



MODEL NA	ME CAPACI	TY	WHEELBASE
SMV 52-12	00 B 52 tons	at 1200 mm	6000 mm
SMV 55-12	00 B 55 tons	at 1200 mm	6000 mm



MODEL NAME	CAPACITY	WHEELBASE
SMV 42-1200 B	42 tons at 1200 mm	5500 mm
SMV 45-1200 B	45 tons at 1200 mm	5500 mm
SMV 50-1200 B	50 tons at 1200 mm	6000 mm



WHEELBASE



MODEL NAME	CAPACITY	WHEELBASE
SMV 3 ECB 80	8 tons at 1220 mm	3750 mm
SMV 4 ECB 80	8 tons at 1220 mm	3750 mm
SMV 5 ECB 80	8 tons at 1220 mm	3750 mm
SMV 6 ECB 80	8 tons at 1220 mm	3750 mm



MODEL NAME	CAPACITY	WHEELBASE
SMV 4/5 ECB 100 DS*	10 tons at 1220 mm	4500 mm
SMV 5/6 ECB 100 DS*	10 tons at 1220 mm	4500 mm
SMV 6/7 ECB 100 DS*	10 tons at 1220 mm	4500 mm

\*DS = Double-stacking spreader

w cabin 4 high		
30 tons		<b>117</b>
0		
KONECRAN	ES	

SMV 37 G4S 35/33 tons at 1490/1730 mm 5000 mm

NAME	CAPACITY	WHEELBASE
NAIVIE	CAPACITY	WHEELBASE
3 G3-G4	30/26 tons at 1490/1730 mm	4750 mm

WHEELBASE



MODEL NAME	CAPACITY	WHEELBASE
SMV 45 G4S-G5S	42/41 tons at 1490/1730 mm	5500 mm
SMV 52 G4S-G5S	45/43 tons at 1490/1730 mm	6000 mm



MODEL NAME	CAPACITY	WHEELBASE
SMV 10-1200 B	10 tons at 1200 mm	3250 mm
SMV 13.6-600 B	13.6 tons at 600 mm	3250 mm



MODEL NAME	CAPACITY	WHEELBASE
SMV 15-1200 B	15 tons at 1200 mm	3750 mm
SMV 16-1200 B	16 tons at 1200 mm	3750 mm
SMV 18-600 B	18 tons at 600 mm	3750 mm
SMV 18-900 B	18 tons at 900 mm	3750 mm



CAPACITY	WHEELBASE
22 tons at 1200 mm	4250 mm
23.6 tons at 1200 mm	4250 mm
25 tons at 1200 mm	4250 mm
	22 tons at 1200 mm 23.6 tons at 1200 mm



MODEL NAME	CAPACITY	WHEELBASE	IV
SMV 28-1200 B RoRo	28 tons at 1200 mm	4500 mm	S
SMV 32-1200 B RoRo	32 tons at 1200 mm	4750 mm	S
			S



SE	MODEL NAME	CAPACITY	WHEE
	SMV 60-1500 B	60 tons at 1500 mm	6000
	SMV 65-1200 B	65 tons at 1200 mm	6000